

LABNET INTERNATIONAL, INC.

MINI INCUBATOR

Labnet
Labnet International, Inc.



- ❑ Ideal for microbiology or hematology applications
- ❑ Corrosion resistant chamber
- ❑ Three shelf levels
- ❑ Door with large viewing area
- ❑ Pilot light to indicate heating
- ❑ Automatic safety cut-out to prevent overheating

SPECIFICATIONS

Exterior dimensions (WxDxH)	11.2 x 11 x 13.2 in / 28.5 x 28 x 33.5 cm
Interior dimensions (WxDxH)	9 x 7.9 x 7.9 in / 23 x 20 x 20 cm
Weight	18.4 lb / 8.3 kg
Capacity	0.375 cu. ft.
Temperature range	ambient +5° to 60°C
Controls	analog
Stability	±0.6°C at 37°C (N.I.S.T. traceable thermometer)
Uniformity	0.65°C at 37°C
Electrical	120V~, 50/60Hz, 0.6A; 230V~, 50/60Hz, 0.3A

ORDERING INFORMATION

Catalog No.	Description
I5110	Mini Incubator, compact general purpose, 115V
I5110-230V	Mini Incubator, compact general purpose, 230V
I5110-shelf	Additional shelf, 22 x 18cm
W0020-110C	Non-toxic, teflon coated thermometer for -20 to 110°C, with 1° resolution, 305mm long, 76mm immersion

Labnet
Labnet International, Inc.

P.O. Box 841 • Woodbridge, NJ 07095 • USA • website: <http://www.labnetlink.com>
US Office • toll free: 888-522-6381 • fax: 732 417-1750 • e-mail: labnet@labnetlink.com
International Office • phone: +1-732-417-0700 • fax: +1-732-417-1750
e-mail: international@labnetlink.com